

Oculer EM-Check® Surface Contamination Test

OC-ENV-02 Microbial Detection Kit



The Oculer EM-Check Surface Microbial Detection Kit is an all-inclusive, ready-to-use kit which simplifies and quickens the process of environmental surface testing for biological contamination. The kit uses Oculer's Rapid 930 Series Technology for the automated detection of microbial activity on cleanroom surfaces using a design that reduces the likelihood of sample cross-contamination and mishandling of samples by the operator.

The OC-ENV-02 kit is intended to be used with the Oculer 930 Series automated reader. The reader's internal LED sends light to the polymer sensor located in the kit vial. The optical system detects the decay of the fluorescence signal emission, which correlates to the oxygen depletion over time due to the respiration of microorganisms in the sample. The system is flexible and allows either enumeration produced from an internal calibration, or a pass/fail test based on presence/absence of oxygen depletion over time. The instrument software allows continuous measurements of oxygen depletion within the reader or endpoint measurements from externally incubated samples.

The OC-ENV-02 kit with Oculer's dedicated reader offers:

- A traditional, growth-based method with enhanced sensitivity due to the oxygen sensing technology
- Non-destructive testing allows further analysis or speciation by traditional methods
- Suitability for Class A/ISO 5 classified areas and lower
- An ideal way to sample the most critical and hard-to-reach points identified by risk assessment
- High recovery of surface microbial contaminants using certified flocked swabs
- Faster time-to-result by using an oxygen-sensitive probe assay
- Automated sample analysis eliminating human reading subjectivity
- Up to 24 samples can be automatically processed per carousel

BENEFITS

Time-to-Result

- Achieve results typically within 24 hours
- Increase sensitivity by maximising recovery
- Advanced test tracking and reliability

Cost Saving

- Easier disposal than agar plates
- No extra costs and risks due to reagent dispensing
- Reduces risks of false positives in aseptic production areas and related investigations

Test Ready

- Fully prepared and disposable
- Minimizes operator handling
- Eliminates unintended contamination

Reduced Operator Handling

- Decreases time-consuming and operator-dependent manipulations
- Simplified standard operating procedures
- Faster sampling steps
- Easy lift-out interchangeable carousel

FEATURES

- Oculer standard culture media
- FLOQSwab™ flocked swab with SRK™ for highest recovery swabbing (>70% each lot).
- Reduced variability on results
- Eliminate cleaning validation studies for culture media residues required for contact plate method
- Compact design and low maintenance reader
- Integrated incubator
- Intuitive screen monitor
- Easy-to-read dashboard with tabular graphics
- Result as Presence/Absence or as colony forming units (CFU)
- Secure results and 21 CFR part 11 and EU GMP Annex 11 compliance
- Compatible with Microsoft Windows 10®

APPLICATIONS

- Microbiological surface sampling in cleanrooms and associated controlled environments
- Microbiological monitoring of equipment, operator clothing and gloves
- Easy monitoring of critical point in RABS and isolators

Bringing Microbiology to Light

Oculer EM-Check® Surface Contamination Test
OC-ENV-06 Microbial Detection Kit



Surface Detection Kit

Materials	Each individual gamma irradiated peel pouch kit contains: - EM-Check® Vial: polypropylene vial with integrated platinum porphyrin polymer and 10 ml of TSB - FLOQSwab: flocced swab in polypropylene tube with sponge and 1ml of Surface Rinse Kit™ (SRK)	
Dimensions	EM-Check® Vial - 15 ml capacity vial: - 120 mm length including red stopper - 17 mm diameter	Swab tube: - 175 mm total length including green stopper - 12 mm external diameter
Filling Volume	10 ml	
Media	Oculer Tryptic Soy Broth based nutrient broth	
Additives	Neutralizers included in the SRK buffer	
Packaging Option	Two bags containing five kits each are triple-bagged together, 20 of the triple-bagged units can be placed inside a fourth plastic bag to produce a final package containing a total of 200 vial kits.	
Storage Temperature	5 °C - 25 °C (41 °F to 77 °F)	
Approximate Detection	10 ⁰ to 10 ⁸ cells	

Oculer Rapid 930 Series Automated Reader

Model	Model 930-15 uses 15 ml capacity vials	Operating Temperature	18 °C to 24 °C (64.4 °F to 75.2 °F)
Test capacity	24 vials	Storage Temperature	10 °C to 35 °C (50 °F to 95 °F)
Throughput	Up to 216 tests in pass/fail mode	Relative Humidity	0 - 95% non-condensing
Power (adaptor supplied)	100-240 VAC, 50-60 Hz Output 72 W max	Dimensions (H x W x D)	31.8 x 30.50 x 38.14 cm (12.52 x 12.01 x 15.02 in)
USB ports	1 USB peripheral port 1 external Barcode Reader port	Weight	12.30 kg (27.12 lbs)
Internal Incubation Temperature	Ambient 2 °C to 40 °C (35.6 °F to 104 °F)	Accessories	Laptop computer (pre-loaded with Oculer software), extra carousel (24 places), external Barcode Reader
Language	Manageable by end-user		

The OCUSwab™ vial uses Oculer Rapid 930 Series® Technology; Rapid 930 Series® is a registered trademark of Oculer Ltd.
 FLOQSwab™ and Surface Rinse Kit™ (SRK) are trademarks of COPAN Diagnostics Inc.
 Windows 10® is a registered trademark of Microsoft Inc.
 All other trademarks are the property of their respective company.
 Oculer Ltd reserves the right to change specifications without notice.
 © 2022 Oculer Limited. All rights reserved.

